

MANIFOLDS




SIMPLE MANIFOLD

3736



- Simple manifold
- M22x1,5 side connections
- Finishing sandblasted yellow or nickel-plated
- Thread ISO 228 and METRIC
- Temperature range min 0°C - max +95°C

Manifold particularly suitable for distributing sanitary or thermal fluids. Plumbing and heating systems and industrial sector are the ideal fields of application.



COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Body	1	CW617N UNI-EN 12165

DIMENSIONS

N. OF WAY	R	A	I	B	D	PN
2	3/4"	M22x1,5	35	83	16,1	10
2	1"	M22x1,5	35	90	16,1	10
3	3/4"	M22x1,5	35	118	16,1	10
3	1"	M22x1,5	35	125	16,1	10
4	3/4"	M22x1,5	35	153	16,1	10
4	1"	M22x1,5	35	158	16,1	10
5	3/4"	M22x1,5	36	190	16,1	10
5	1"	M22x1,5	36	195	16,1	10

PACKAGING

	2 WAY 3/4"	2 WAY 1"	3 WAY 3/4"	3 WAY 1"	4 WAY 3/4"	4 WAY 1"	5 WAY 3/4"	5 WAY 1"
NICKEL-PLATED	37361206	37361208	37361306	37361308	37361406	37361408	37361506	37361508
YELLOW	37360206	37360208	37360306	37360308	37360406	37360408	37360506	37360508
PCS BAG	-	-	-	-	-	-	-	-
PCS CARTON	80	50	50	40	50	50	40	30