### WATER COMPRESSION FITTINGS


imonod **o** 


COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

# **MALE STRAIGHT FITTING**

3892







#### • Male straight compression fitting with O-Ring

- Thread ISO 228
- Maximum operating pressure: 10 bar
- Temperature range min 0°C max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, air-conditioning and distribution of drinking water.

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

#### COMPONENTS

| POS. | PART NAME           | N° | MATERIAL                          |
|------|---------------------|----|-----------------------------------|
| 1    | Fitting             | 1  | CW617N UNI-EN 12164 nickel-plated |
| 2    | O-Ring              | 2  | EPDM Perox                        |
| 3    | Washer              | 1  | PTFE                              |
| 4    | O-Ring (18,77x1,78) | 2  | EPDM Perox                        |
| 5    | Ogive               | 1  | CW617N UNI-EN 12164               |
| 6    | Nut                 | 1  | CW617N UNI-EN 12165 nickel-plated |

## DIMENSIONS

| Α    | R    | В  |  |
|------|------|----|--|
| 16x2 | 1/2" | 38 |  |
| 20x2 | 1/2" | 41 |  |

#### PACKAGING

|            | 16 - 1/2" | 20 - 1/2" |  |
|------------|-----------|-----------|--|
| CODE       | 38921604  | 38922004  |  |
| PCS BAG    | 10        | 10        |  |
| PCS CARTON | 250       | 150       |  |