



COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

MALE STRAIGHT FITTING

3892



- Male straight compression fitting with O-Ring
- Thread ISO 228
- Maximum operating pressure: 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, air-conditioning and distribution of drinking water.

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS

| POS. | PART NAME | N° | MATERIAL |
|------|---------------------|----|-----------------------------------|
| 1 | Fitting | 1 | CW617N UNI-EN 12164 nickel-plated |
| 2 | O-Ring | 2 | EPDM Perox |
| 3 | Washer | 1 | PTFE |
| 4 | O-Ring (18,77x1,78) | 2 | EPDM Perox |
| 5 | Ogive | 1 | CW617N UNI-EN 12164 |
| 6 | Nut | 1 | CW617N UNI-EN 12165 nickel-plated |

DIMENSIONS

| A | R | B |
|------|------|----|
| 16x2 | 1/2" | 38 |
| 20x2 | 1/2" | 41 |

PACKAGING

| | | |
|-------------|-----------------|-----------------|
| | 16 - 1/2" | 20 - 1/2" |
| CODE | 38921604 | 38922004 |
| PCS BAG | 10 | 10 |
| PCS CARTON | 250 | 150 |