



COMPRESSION FITTINGS FOR PEX-AL-PEX
PIPES

MALE STRAIGHT FITTING

3901



- Male straight compression fitting
- Thread EN 10226-1
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water.

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165 (hot pressed) nickel-plated - CW617N UNI-EN 12164 (from bar) nickel-plated
2	O-Ring	2	EPDM Perox
3	Washer	1	PTFE
4	Ogive	1	CW617N UNI-EN 12164
5	Nut	1	CW617N UNI-EN 12165 nickel-plated

DIMENSIONS

A	R	B
16x2	3/8"	34
16x2	1/2"	38
16x2	3/4"	39
18x2	1/2"	37,5
18x2	3/4"	40,5
20x2	1/2"	41
20x2	3/4"	41,5
26x3	3/4"	48,5
26x3	1"	51
32x3	1"	59

PACKAGING

	16 - 3/8"	16 - 1/2"	16 - 3/4"	18 - 1/2"	18 - 3/4"	20 - 1/2"	20 - 3/4"	26 - 3/4"	26 - 1"	32 - 1"
CODE	39011603	39011604	39011606	39011804	39011806	39012004	39012006	39012606	39012608	39013208
PCS BAG	10	10	10	10	10	10	10	5	5	5
PCS CARTON	250	250	200	200	150	150	150	100	100	50