



COMPRESSION FITTINGS FOR PEX-AL-PEX
PIPES

FEMALE STRAIGHT FITTING

3902



- Female straight compression fitting
- Thread EN 10226-1
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water.

The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS			
POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165 nickel-plated
2	O-Ring	2	EPDM Perox
3	Washer	1	PTFE
4	Ogive	1	CW617N UNI-EN 12164
5	Nut	1	CW617N UNI-EN 12165 nickel-plated

DIMENSIONS		
A	R	B
16x2	1/2"	37
16x2	3/4"	39,5
18x2	1/2"	35
18x2	3/4"	37
20x2	1/2"	37,5
20x2	3/4"	40
26x3	3/4"	41
26x3	1"	45,5
32x3	1"	50

PACKAGING

	16 - 1/2"	16 - 3/4"	18 - 1/2"	18 - 3/4"	20 - 1/2"	20 - 3/4"	26 - 3/4"	26 - 1"	32 - 1"
CODE	39021604	39021606	39021804	39021806	39022004	39022006	39022606	39022608	39023208
PCS BAG	10	10	10	10	10	10	5	5	5
PCS CARTON	200	180	200	150	150	150	100	80	50