



COMPRESSION FITTINGS FOR PEX-AL-PEX PIPES

FEMALE ELBOW FITTING

3954



- Female flanged elbow compression fitting
- Thread EN 10226-1
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water. The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS

POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165 nickel-plated
2	O-Ring	2	EPDM Perox
3	Washer	1	PTFE
4	Ogive	1	CW617N UNI-EN 12164
5	Nut	1	CW617N UNI-EN 12165 nickel-plated

DIMENSIONS

A	R	B	C
16x2	1/2"	32	41
16x2	3/4"	37	45
18x2	1/2"	37	47
18x2	3/4"	39	50
20x2	1/2"	37	44

PACKAGING

	16 - 1/2"	16 - 3/4"	18 - 1/2"	18 - 3/4"	20 - 1/2"
CODE	39541604	39541606	39541804	39541806	39542004
PCS BAG	10	5	10	5	10
PCS CARTON	100	70	80	70	80