



COMPRESSION FITTINGS FOR PEX-AL-PEX  
PIPES

STRAIGHT COMPRESSION  
FITTING WITH SWIVEL NUT

3906



- Straight compression fitting with swivel nut
- Thread ISO 228
- Maximum operating pressure 10 bar
- Temperature range min 0°C - max +95°C

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, HVAC, air-conditioning and distribution of drinking water. The fitting features an external clamping nut to ensure a perfect crimping to the pipe and an excellent resistance to external stress.

COMPONENTS

| POS. | PART NAME    | N° | MATERIAL                          |
|------|--------------|----|-----------------------------------|
| 1    | Fitting      | 1  | CW617N UNI-EN 12165 nickel-plated |
| 2    | O-Ring       | 2  | EPDM Perox                        |
| 3    | Washer       | 1  | PTFE                              |
| 4    | Ogive        | 1  | CW617N UNI-EN 12164               |
| 5    | Nut          | 1  | CW617N UNI-EN 12165 nickel-plated |
| 6    | Elastic ring | 1  | Stainless steel                   |
| 7    | Nut          | 1  | CW617N UNI-EN 12164 nickel-plated |
| 8    | Gasket       | 1  | Fasit Omnia                       |

DIMENSIONS

| A    | R    | B  |
|------|------|----|
| 16x2 | 1/2" | 50 |

PACKAGING

|            |           |
|------------|-----------|
|            | 16 - 1/2" |
| CODE       | 39061604  |
| PCS BAG    | 20        |
| PCS CARTON | 200       |