



PRESS FITTINGS FOR PEX-AL-PEX PIPES

MALE ELBOW FITTING

4053



- Male elbow press fitting
- Maximum operating pressure 10 bar
- Thread EN 10226-1
- Temperature range min 0°C - max +95°C
- The jaws for the fittings pressing have to be **TH** profile.

Fitting suitable for distributing fluids that are generally non-corrosive, compatibly with the fitting materials. Heating, plumbing and industrial systems are the ideal fields of application, such as high and low temperature heating systems, air-conditioning and distribution of drinking water. The tightness is guaranteed by two EPDM PEROX O-Rings, particularly recommended with water-glycol solutions, with a maximum glycol presence of 50%. The steel sleeve pressing, carried out with electromechanical tools, ensures a perfect and indivisible crimping to the pipe as well as an excellent resistance to external stress.

ACS

COMPONENTS			
POS.	PART NAME	N°	MATERIAL
1	Fitting	1	CW617N UNI-EN 12165
2	O-Ring	2	EPDM Perox
3	Washer	1	PTFE
4	Bushing	1	AISI 304 stainless steel

DIMENSIONS			
A	R	B	C
16	3/8"	49	30
16	1/2"	49	35
18	1/2"	50	35
20	1/2"	50	35
20	3/4"	50	35
26	3/4"	52	43
26	1"	52	41
32	1"	55	46

FOLLOWING THE DIMENSIONS FROM 40 TO 63

PACKAGING

	16 - 3/8"	16 - 1/2"	18 - 1/2"	20 - 1/2"	20 - 3/4"	26 - 3/4"	26 - 1"	32 - 1"
CODE	40531603	40531604	40531804	40532004	40532006	40532606	40532608	40533208
PCS BAG	10	10	10	10	10	5	5	5
PCS CARTON	200	200	150	150	100	80	50	50