



WATER BALL VALVES

**NIAGARA**

7710



- F/F miniball valve with screwdriver slot
- Thread ISO 228
- Temperature range min -10°C - max +90°C
- Normal pressure max 10 bar

Valve suitable for distributing and interrupting fluids that are generally non-corrosive, compatibility with the valve materials. Excellent fields of application are in plant engineering for plumbing, heating and pneumatics and industry, when it is necessary to have a shut-off element with reduced dimensions. It is a reduced-bore valve, and ball seal is provided by two PTFE seats. The operating mechanism seal features an O-Ring with an internally installed stem and anti-ejection system.

It is advisable to carry out a complete maneuver cycle at least once every three months in order to prevent limescale deposits that could compromise the valve functioning.

**COMPONENTS**

POS	PART NAME	N°	MATERIAL
1	Body	1	CW617N UNI-EN 12164 chrome-plated
2	Seal	2	PTFE
3	Ball	1	CW617N UNI-EN 12164 nickel-plated
4	Ring nut	1	CW617N UNI-EN 12164
5	Stem	1	CW617N UNI-EN 12164 nickel-plated
6	O-Ring	1	NBR

**DIMENSIONS**

DN	A	B	D	PN
8	1/4"	39	8	10
10	3/8"	42	8	10
15	1/2"	47	10	10
20	3/4"	54	12	10

**PACKAGING**

	1/4"	3/8"	1/2"	3/4"
<b>CODE</b>	<b>77100002</b>	<b>77100003</b>	<b>77100004</b>	<b>77100006</b>
PCS BOX	30	30	20	15
PCS CARTON	300	300	200	150